TOWN OF LOOMIS STORMWATER QUALITY DIVISION

Car Washing

Best Management
Practices

Everyone should be aware that the discharge of pollutants into the storm drainage system, or into surrounding water bodies, is prohibited by local ordinance and state and federal law. It is your responsibility to keep pollutants, like car wash water, out of the storm drainage system and local waterways.

If car washing is a central activity of your business, follow these tips:

- Since commercial vehicle washing discharges cannot be discharged to the storm drain, you must construct a wash pad that drains to the sanitary sewer. The pad should be covered with a roof and surrounding grades sloped away from the wash area, or the wash area should be bermed, to prevent additional drainage, such as stormwater runoff, from entering the sanitary sewers.
- Treat and recycle wash water to minimize water use and sanitary sewer discharges.
- Install an oil/grit separator if required by the sewer agency or building department.

If car washing is an occasional activity of your business, follow these tips:

- Avoid washing vehicles on site. Take vehicles to a commercial car wash that is properly connected to the sanitary sewer, or dry cloth the vehicles.
- If car washing is provided as a courtesy benefit to your customers, consider providing a voucher for a properly equipped commercial car wash instead.

CAR WASHING

Additional practices for bile sales lots:

- Fleet and sales lot ow with solvents or clear protective coatings fr charges of these mate drain is never allowe
- Employees or contract cleaning agents on flet lots must collect the and discharge it to the is not permissible to evaporate, as the polleft behind and will be sequent rainfall.

If washing your car at ho tips:

- Using a commercial properly equipped is
- ♦ If you choose to was



TOWN OF LO Qualit Phone: (9 6140 Horseshoo Loomis

Household Hazardo Disposal and Recyc Information

Phone: (916) 543-39 Or visit us on the whttp://www.wpwma